

Technical Specifications

imagePROGRAF PRO-2000

TECHNOLOGY

Printer Type	12 Colour 24"/610mm
Print Technology	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)
Number of Nozzles	18,432 nozzles (1536 nozzles x 12 colour)
Print Resolution	2,400 dpi x 1200 dpi
Nozzle Pitch	600 dpi x 2 includes Non-firing nozzle detection and compensation system
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
Ink Droplet Size	minimum 4 pl per colour
Ink Capacity	Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 160ml
Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser
OS Compatability	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11 SG Raster (Swift Graphic Raster)
Printer Languages	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b
Standard Interfaces	

MEMORY

Standard memory	1 GB
Hard Drive	320 GB

PRINTING PAGE SIZE/ PRINT SPEED

Plain Paper
Coated Paper
Photo Glossy Paper

MEDIA HANDLING

Media Feed and Output	Roll Paper: One Roll, Front-loading, Front Output Optional Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 - 610 mm Cut sheet: 203.2 - 610 mm
Media Thickness	Roll/Cut: 0.07 - 0.8 mm
Minimum Printable Length	203.2 mm
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
Maximum Media Roll Diameter	170 mm
Media Core Size	Internal diameter of roll core: 2 1/3"
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm
Margins Printable area	Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Media Feed Capacity

Media Take-up roll unit

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) & Weight (Kg)

Packaged Dimensions WxDxH (mm) & Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Acoustic Noise (Power/ Pressure)

Regulations

Environment Certificates

WHAT'S INCLUDED

What's in the Box?

Software Included

WHAT'S INCLUDED

Optional Items

CONSUMABLES

User Replaceable Items

Roll Paper: One roll. If second option is added then automatic switching is possible

Optional - Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24", 257 mm (JIS B4)*, 297 mm (ISO A3)*, 329 mm (ISO A3+)*, 420 mm (ISO A2)*, 8 1/4", 16 1/4", 300 mm*

*Some environmental conditions may not produce the desired result

Standard position: 1 sheet

Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1110 x 984 x 1168 (Basket Opened)

1110 x 766 x 1168 (Basket Closed)

Weight: approx 101 kg (including Roll Holder Set, excluding ink and print heads)

Printer (Main unit with pallet): 1322 mm x 900 mm x 1035 mm

Weight: approx: 122 kg

Stand/Basket: 1109 mm x 795 mm x 217mm,

Weight: approx: 22 kg

AC 100-240V (50-60Hz)

Operation: 88 W or less

Standby: 1.8 W or less

Power off: 0.5 W or less

Temperature: 15-30°C, Humidity: 10-80% RH
(no dew condensation)

Operation: TBD dB (A) (Glossy paper, Print priority: Standard)

Standby: TBD dB (A) or less

Operation: TBD Bels or less

(Glossy paper, Image, Print priority: Standard)
(Measured on ISO7779 standard)

Europe: CE mark, Germany: TUV mark, Russia: EAC,
Other countries: CB certification

International Energy Star Program (WW), RoHS

Printer, 1x print head, 3" paper core attachment, EU & UK Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

Printer Stand: SD-21

Roll Unit: RU-21

2 1/3" Roll Holder: RH2-27

Ink Tank: PFI-1100(160ml), PFI-1300(330ml), PFI-1700(700ml)

Print Head: PF-10

Cutter Blade: CT-07

Maintenance Cartridge: MC-30



Crystal-fidelity

