Specifications: iPF680/iPF685

	imagePROGRAF iPF680	imagePROGRAF iPF685
TECHNOLOGY		
Printer Type	5 Colour - 24"/609.6 mm	
Print Technology	Canon inkjet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each	
Print Resolution	2,400 x 1,200dpi	
Nozzle Pitch	1,200dpi x 2	
Juaranteed Minimum Line Width	0.02 mm	
Line Accuracy	±0.1% or less	
Ink Droplet Size	4 Picoliter per colour	
Ink Capacity	Bundled Starter Ink: 90 ml (Only MBK 130 ml) Sales Ink: 130 ml and 300 ml	
Ink Type	Dye/Pigment Reactive Ink Dye: Cyan, Magenta, Yellow, Black Pigment: Matte Black	
OS Compatibility	32 bit - Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003/2003R2, Windows Server 2008 64 bit - Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003/2003R2, Windows Server 2008/2008R2, Windows Server 2012/2012R2 Mac: OSX - 10.6.8-OS10.9.x	
Printer Languages	GARO (Graphic Arts Language with Raster Operations), HP-GL/2, HP RTL	
Standard Interfaces	USB 2.0 High-Speed Ethernet 10/100/1000 Base-T/TX	
Stanuaru miterraces	Ethernet 10/100	High-Speed J/1000 Base-T/TX
PRINTING SPEED	Ethernet 10/100	High-Speed)/1000 Base-T/TX
	Ethernet 10/100	High-Speed //1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode)
PRINTING SPEED	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi)/1000 Base-T/TX
PRINTING SPEED A1 Size, Plain Paper	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi	1/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode)
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi	1/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode)
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper MEMORY	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa	y/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper MEMORY Buffer RAM	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB	in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB)
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper MEMORY Buffer RAM Hard Drive	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A Roll Paper: 10°/254	in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB)
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper MEMORY Buffer RAM Hard Drive PAPER HANDLING	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 m 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A Roll Paper: 10"/254 Cut Sheet: 8"/203.2 Roll Unit: 0.	y/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB) 320GB mm - 24*/609.6 mm
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper Buffer RAM Hard Drive PAPER HANDLING Media Width	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A N/A Roll Paper: 10"/254 Cut Sheet: 8"/203.2 Roll Unit: 0. Top Loading Manual Roll: 20	v/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB) 320GB mm - 24"/609.6 mm mm - 24"/609.6 mm 07 - 0.8 mm
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper Buffer RAM Hard Drive PAPER HANDLING Media Width Media Thickness Minimum Printable	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A N/A Roll Paper: 10"/254 Cut Sheet: 8"/203.2 Roll Unit: 0. Top Loading Manual Roll: 20 Cut Sheet:	v7 000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB) 320GB mm - 24"/609.6 mm m - 24"/609.6 mm 07 - 0.8 mm Feed: 0.07 - 0.8 mm 03.2 mm
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper A1 Size, Coated Paper Buffer RAM Hard Drive PAPER HANDLING Media Thickness Minimum Printable Length Maximum Printable	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A Roll Paper: 10"/254 Cut Sheet: 8"/203.2 Roll Unit: 0. Top Loading Manual Roll: 22 Cut Sheet: 18 m (Varies according to	v/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB) 320GB mm - 24"/609.6 mm m - 24"/609.6 mm 07 - 0.8 mm Feed: 0.07 - 0.8 mm 3.2 mm 279.4 mm
PRINTING SPEED A1 Size, Plain Paper A1 Size, Coated Paper Buffer RAM Hard Drive PAPER HANDLING Media Width Media Thickness Minimum Printable Length Maximum Printable Length	Ethernet 10/100 0:25 min (Fast Economy Mode), 0:28 mi 0:43 min (Fast Mode), 1:17 min (Standa 256MB N/A Roll Paper: 10"/254 Cut Sheet: 8"/203.2 Roll Uni: 0. Top Loading Manual Roll: 20 Cut Sheet: 18 m (Varies according to 150. Roll Feed: One Roll, To	v/1000 Base-T/TX in (Fast Mode), 0:42 min (Standard Mode) ard Mode), 2:05 min (High Quality Mode) 32GB (Physical Memory 256MB) 320GB mm - 24"/609.6 mm mm - 24"/609.6 mm 07 - 0.8 mm Feed: 0.07 - 0.8 mm 32.79.4 mm 279.4 mm to the OS and application)

PRINTER MODEL	imagePROGRAF iPF680	imagePROGRAF iPF685
DIMENSIONS AND WEIGHT		
Physical Dimensions (W x D x H)	Main Unit: 997 (W) x 757 (D) x 492 (H) mm (Excluding consumables and printer stand) Main unit with a printer stand and basket open: 997 (W) x 887 (D) x 1,062 (H) mm Main Unit with basket in extended postion for flatbed stacking: 997 (W) x 1100 (D) x 1062 (H) mm	
Weight	46.0 kg (Main unit) 56.7 kg (Main Unit + Printer stand)	46.2 kg (Main unit) 56.9 kg (Main unit + Printer stand)
Software Included	Canon Printer Driver, Status Monitor/Print Monitor, ExtraKit – Free Layout and iR enlargement Copy, Printer Driver Optimization Module for AutoCAD, Media Configuration Tool, PosterArtist Lite (PC only), Print Plug-in for Microsoft [®] Word/Excel/PowerPoint (PC only) Direct, Print & Share utility, Custom Installer Creation Tool	
POWER AND OPERATING REQUIREMENTS		
Power Supply	AC 100 - 240 V (50-60 Hz)	
Power Consumption	Operation: 140 W or less Power Off Standby: 0.5 W or less	
Operating Environment	15 - 30°C, 10 - 80 % (Condensation free)	
Noise Level (Approx.)	Operation: approx. 47 dB Standby: 35 dB or less Accoustic Power: 6.4 Bels Based on ISO 7779	
Regulations	Europe: CE mark, Germany: TUV mark, Russia: EAC Other Countries: CB Certification	
Environment Certificates	ENERGY STAR (Japan) (USA) (EU), RoHS Directive (WW), The ECO Declaration (TED) (Europe), WEEE (Europe)	
WHAT'S INCLUDED		
What's In The Box?	Hex wrench screwdriver, 1 print head, 1 set of starter ink tanks (C, M, Y, BK - 90ml/MBK – 130 ml), 3 inch core adapters setup guide, User software CD-ROM (Mac & Win), Carrying caution leaflet, Safety/Standard Environment leaflet, PosterArtist Lite leaflet, PosterArtist Lite software CD-ROM, EAC leaflet, Quick guide	
OPTIONS		
Printer Stand	ST-27	
Roll Holder Set	RH2-26	
CONSUMABLES		
Ink Tanks	PFI-107: 130 ml – MBK/BK/C/M/Y PFI-207: 300 ml – MBK/BK/C/M/Y	
Print Head	PF-04	
Maintenance Cartridge	MC-10	

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaftet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.¹⁰ and 00: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc

canon.com

Canon Europe canon-europe.com

Full-photolithography Inkjet

English Edition © Canon Europa N.V., 2014



Canon Europe Ltd 3 The Square Stockley Park Uxbridge Middlesex UB11 1ET United Kingdom

